



**PRINTS UP TO 2 LINES OF ALPHANUMERICS
IP55 WASHDOWN-RATED**

LINX 4900

KEY FEATURES

- **Prints up to 2 lines of alphanumerics** on virtually any material thanks to a broad range of LINX inks available.
- **Production line speeds** – up to 1,230 feet/minute.
- **Stainless steel case** – has no dirt traps and provides a surface which liquid naturally slides off.
- **Single button** startup and shutdown.
- **IP55 washdown rating** – perfect for food, beverage and dairy packaging plants where washdown and harsh environments are demanding on equipment.
- **Simple menu-driven interface** – with message preview for error-free code creation.
- **50 message memory store** – and automatic date creation minimize the need for editing.
- **Sealed robust printhead** requires no manual adjustments, removing the risk of damage to critical components.
- **Easy to clean** as casing is free of doors and other dirt traps.
- **Self-cleaning printhead and automatic power down** give mess-free, trouble-free start-ups and stops.
- **No need to stop or open the printer to refill** so production is not disrupted.
- **Small compact design** allows for quick and easy installation and mobility.



Specifications

| Print | 4900 |
|--|----------------|
| Printhead with 2M conduit, standard | MK7 |
| Printhead/conduit options | 4M, 90D |
| Max lines of print | 2 |
| Character Height Range | 0.08" to 0.30" |
| Max speed; single line print | 1,230 fpm |
| Ink Range | Dye based |
| Automatic date codes, sequential numbering | Yes |
| Timed messages | Yes |
| Graphics/Logo printing | No |
| Barcodes, common linear and 2D Datamatrix | No |
| Memory capacity (number of messages) | 50 |

| Connections/Interfacing | 4900 |
|--|----------|
| Touch Screen | No |
| Logojet PC Based message and logo creation software and DDE Driver Software | Optional |
| RS232 port | Yes |
| Ethernet Option | No |
| Parallel I/O Option | No |
| USB port for message and printer setting back up and restore | No |
| Shaft encoder, product detector, external single stage alarm, volt-free contact alarm connection | Yes |

| Other | 4900 |
|---------------------------------------|----------------------------|
| Ingress Protection rating | IP55 |
| Base and Enclosure | Stainless Steel |
| Operating temperature range | 41-113°F |
| Humidity Range (r.h., non-condensing) | 90% max |
| Power Supply | 100-230V 50/60 Hz |
| Power Consumption | 200W |
| Weight | 44 lbs |
| Regulatory approvals | TÜV/GS, CE mark, FCC, RoHS |